

# EZVIEW 20MM RED/AMBER OUTDOOR DIGITAL DISPLAY

*I am quite pleased with our **Electronic Message Center**.  
It's **attracted much attention** to our new bank branch,  
and has served as an effective addition to our regular advertising.*



## Check out the Adaptive advantage.



### The best image quality

Expect high-resolution, contrast-rich graphics that have been hailed as the best in the business.



### All-weather protection

Only Adaptive gives you the Protector case, the ventless solution that seals out the elements, and guards your investment for years to come.



### Outstanding value

With a cost that no other display can even approach, our new EZView line offers all of the above, along with an unmatched support network.

# EzView 20mm Red/Amber Digital Display Specifications

Rows	Columns	Height (Inches)	Length (Inches)	Power (Amps) 115VAC Typical	Weight
16	96	12.6"	75.6"	.3	70 lbs.
16	112	12.6"	88.2"	.4	85 lbs.
16	128	12.6"	100.8"	.5	95 lbs.
16	144	12.6"	113.4"	.5	105 lbs.
16	160	12.6"	126"	.6	120 lbs.
16	176	12.6"	138.6"	.6	130 lbs.
32	96	25.2"	75.6"	.7	140 lbs.
32	112	25.2"	88.2"	.8	165 lbs.
32	128	25.2"	100.8"	.9	185 lbs.
32	144	25.2"	113.4"	1.0	210 lbs.
32	160	25.2"	126"	1.1	235 lbs.
32	176	25.2"	138.6"	1.2	255 lbs.
48	96	37.8"	75.6"	1.0	210 lbs.
48	112	37.8"	88.2"	1.2	245 lbs.
48	128	37.8"	100.8"	1.4	280 lbs.
48	144	37.8"	113.4"	1.5	315 lbs.
48	160	37.8"	126"	1.7	350 lbs.
48	176	37.8"	138.6"	1.9	385 lbs.
64	96	50.4"	75.6"	1.4	280 lbs.
64	112	50.4"	88.2"	1.6	325 lbs.
64	128	50.4"	100.8"	1.8	370 lbs.

- NOTES**
- Approximate dimensions, power and weight. Due to continuing product innovations, all specifications are subject to change without notice.
  - Additional sizes/configurations available. Call for quote.

<b>Pitch &amp; Model Series:</b>	20mm / 0.79 inch pixel pitch 1 Red / or 1 Amber LED per pixel
<b>LED Color:</b>	4096 Shades
<b>Viewability &amp; Intensity:</b>	110° horizontal/40° vertical; calibrated to 4000 nits
<b>Programming:</b>	Operates with Ooh!Media 2009 content management software (purchased separately)
<b>Controller:</b>	Embedded controller, 1GB FLASH, 16M RAM, ARM9 processor
<b>Connectivity to Controller:</b>	Wired Ethernet with optional Wireless (2.4GHz)
<b>Service Access:</b>	Front-serviceable components. Power, Ethernet, and back-to-back connections through rear service panel.
<b>Case Material:</b>	UL50 type 3R, IP24 aluminum cabinet
<b>Mounting:</b>	Mounting hardware included
<b>Dimming Feature:</b>	Programmable dimming with optional photocell dimming
<b>Graphics Frame Rate:</b>	15 fps

<b>Graphics Capability:</b>	30 Minutes total runtime
<b>Special Features:</b>	Weatherproof case design eliminates external contamination by rain, salt fog or dust and reflects solar radiation  Supports master/slave dual face display  Automatic thermal protection for all electronics  Thermostatically controlled fans for internal cooling  Conformal coating on LED electronics  Optional accessories: wireless communications kit, external temperature and light sensor probe kit, back-to-back communications kit
<b>Temperature:</b>	-22° to 122°F / -30° to 50°C
<b>Limited Warranty:</b>	Two year limited factory depot warranty; 3 year additional extended coverage option available at time of sign purchase. See Adaptive Terms & Conditions for complete warranty details.
<b>Agency Approvals:</b>	ETL to UL 60950-1 C-ETL-US listing mark